

# **DENSO BUTYL 35 TAPE**

**Polyethylene/Butyl Rubber Pipeline Tape - Black**

## **Description**

Denso Butyl 35 Tape is a polyethylene backed tape with a butyl rubber adhesive. Available in black rolls.

## **Uses**

For the long term anti-corrosion protection of small to large diameter pipes including weld joints, fittings, ells and tees and is compatible with coal tar, fusion bond epoxy, asphalt, and polyethylene pipeline coatings.

## **Features**

- Excellent adhesion to pipe and self
- Resistant to UV
- Good conformability and consistent uniform thickness
- Easily applied with no special equipment
- Compatible with common pipe coatings
- Excellent resistance to cathodic disbonding
- Meets AWWA C209 Standard
- Cold applied

## **Application**

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Surface must be clean, dry and free of grease. Peel back interleaving and apply adhesive side of the tape to the surface and press down. Apply the tape spirally with enough tension to make it conform. Remove interleaving as wrapping proceeds. Overlap each turn by at least 1" or 55% to achieve double thickness.

Irregular surfaces such as valves, flanges, etc. may require the use of Denso Mastic or Denso Profiling Mastic. Refer to the product data sheets for these specific products for information on application and selection.



# Denso Butyl 35 Tape

## Property Specifications

PROPERTIES	ENGLISH
Tensile Strength	23 lb/in width
Elongation at Break (ASTM D1000)	250%
Dielectrical Strength (ASTM D1000)	20 kV
Water Vapor Transmission (ASTM E398)	< 0.2 g/100 in <sup>2</sup> /24 hour
Resistance to Hydrocarbons	Good
Resistance to Acids, Alkalis and Salts	Excellent
Temperature Range	
For Application	32°F to 115°F
For Continuous Service	0°F to 160°F
Recommended Holiday Test Voltage	
Single Layer	10 kV
Double Layer	15 kV
Dimensions	
Roll Length	50 feet
Roll Width	2", 4", 6"
Thickness (ASTM D1000)	
Backing	2 mil
Adhesive	33 mil
Total	35 mil
Color	
Backing	Black
Adhesive	Gray

## Quantity Estimates

Tape Width	Rolls*/ Case	Coverage with 1" Overlap	Coverage with 50% Overlap
in.	ea.	ea.	ea.
2"	24	100 ft <sup>2</sup> /case	100 ft <sup>2</sup> /case
4"	12	150 ft <sup>2</sup> /case	100 ft <sup>2</sup> /case
6"	8	167 ft <sup>2</sup> /case	100 ft <sup>2</sup> /case

\*All rolls are 50 feet in length.

Other roll widths are available on request.



### DENSO NORTH AMERICA

HOUSTON:  
9747 Whilhorn Drive,  
Houston, Texas,  
U.S.A. 77095  
Tel: 281-821-3355  
Fax: 281-821-0304

TORONTO:  
90 Ironside Crescent,  
Unit 12, Toronto,  
Ontario, Canada M1X1M3  
Tel: 416-291-3435  
Fax: 416-291-0898

[www.densona.com](http://www.densona.com)

*A Member of Winn & Coales International*

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.